CLG-MERC1.02		Page 1 of 10
Title: Determination of Mercury by Atomic Absorption Spectroscopy		
Revision: 02	Replaces: CLG-MERC1.01	Effective: 04/13/2018

Contents

A.	INTRODUCTION	2
B.	EQUIPMENT	2
C.	REAGENTS AND SOLUTIONS	3
D.	STANDARD(S)	4
E.	SAMPLE PREPARATION	5
F.	ANALYTICAL PROCEDURE	5
G.	CALCULATIONS / IDENTIFICATION	7
H.	SAFETY INFORMATION AND PRECAUTIONS	8
I.	QUALITY ASSURANCE PLAN	9
J.	APPENDIX	10
K.	APPROVALS AND AUTHORITIES	10

CLG-MERC1.02		Page 2 of 10
Title: Determination of Mercury by Atomic Absorption Spectroscopy		ру
Revision: 02	Replaces: CLG-MERC1.01	Effective: 04/13/2018

A. INTRODUCTION

1. Summary of Procedure

A portion of homogenized tissue sample is digested with concentrated sulfuric and nitric acids at 80 °C followed by oxidation with potassium permanganate and potassium persulfate at 30 °C. The sample is diluted to a known volume; an aliquot is removed and analyzed by reducing any contained mercury (Hg) with stannous chloride to elemental mercury. The elemental mercury is measured by a conventional Atomic Absorption Spectrometer or stand alone cold vapor Flow Injection Mercury System.

2. Applicability

This method is suitable for the determination of total mercury (organic + inorganic) in fish of the order Siluriformes (catfish), bovine, swine, and chicken muscle; bovine, swine, and chicken liver; and processed products at levels ≥ 0.2 ppm.

Note: Refer to 21CFR for tolerance values set by FDA and 40CFR for tolerance values set by EPA

B. EQUIPMENT

Note: Equivalent equipment may be substituted.

1. Apparatus

- a. Biochemical Oxygen Demand (BOD) bottle 300 mL with a ground glass stopper.
- b. Centrifuge tubes 15 mL, polypropylene.
- c. Water bath Complete with a covered top and the ability to maintain water at a depth of 2 3 in. at 95 ± 5 °C.
- d. Volumetric flask 1 L.
- e. Graduated cylinders 100 mL, 500 mL, and 1 L

2. Instrumentation

Perkin/Elmer, cold vapor, Flow Injection Mercury System (FIMS) which includes a computer system with software capable of controlling the instrumentation and calculating the final concentrations of Hg in samples. Follow manufacturers suggested instrument settings.

CLG-MERC1.02		Page 3 of 10
Title: Determination of Mercury by Atomic Absorption Spectroscopy		
Revision: 02	Replaces: CLG-MERC1.01	Effective: 04/13/2018

C. REAGENTS AND SOLUTIONS

Note: Equivalent reagents / solutions may be substituted. The maximum length of time that a working reagent shall be used is 1 year unless the laboratory has produced extension data.

1. Reagents

- a. Hydroxylamine Hydrochloride (NH₂OH•HCI) CAS 5470-11-1, Cat. No. 255580, Sigma-Aldrich.
- b. Hydroxylamine Sulfate (NH₂OH)₂•H₂SO₄ CAS 10039-54-0, Sigma-Aldrich, Cat. No. 210250 Optional. May be used as a one-to-one direct substitute for hydroxylamine hydrochloride.
- c. Nitric Acid, Concentrated (HNO₃) CAS 7697-37-2, Cat. No. 258113, Sigma-Aldrich.
- d. Potassium Permanganate (KMnO₄) CAS 7722-64-7, Cat. No. 399124, Sigma-Aldrich.
- e. Potassium Persulfate (K₂S₂O₈) CAS 7727-21-1, Cat. No. 216224 Sigma-Aldrich.
- f. Reagent grade Water ASTM type I or Type II.
- g. Sodium Chloride (NaCl) CAS 7647-14-5, Cat. No. S7653, Sigma-Aldrich.
- h. Stannous Chloride (SnCl₂) CAS 10025-69-1, Cat. No. 31669, Sigma-Aldrich.
- i. Stannous Sulfate (SnSO₄) CAS 7488-55-3, Cat. No. 244635, Sigma-Aldrich Optional. May be used as a one-to-one direct substitute for stannous chloride.
- j. Sulfuric Acid, Concentrated (H₂SO₄) CAS 7664-93-9, Cat. No. 320501, Sigma-Aldrich.

2. Solutions

- a. 12% (w/v) Hydroxylamine Solution:
 - Dissolve 12 g of sodium chloride and 12 g of hydroxylamine hydrochloride (or 12 g of hydroxylamine sulfate) in 70 mL of water in a 100 mL graduated cylinder. Bring to 100 mL with water
- b. 5% (w/v) Potassium Permanganate Solution:
 - Dissolve 5 g of potassium permanganate in 100 mL of water in a graduated cylinder.
- c. 5% (w/v) Potassium Persulfate Solution:

CLG-MERC1.02		Page 4 of 10
Title: Determination of Mercury by Atomic Absorption Spectroscopy		
Revision: 02	Replaces: CLG-MERC1.01	Effective: 04/13/2018

Dissolve 5 g of potassium persulfate in 100 mL of water in a graduated cylinder.

d. 10% (w/v) Stannous Chloride Solution:

To 300 mL of reagent grade water, in a graduated cylinder, add 5.6 mL of concentrated sulfuric acid, and 40 g of stannous chloride (SnCl₂). Dilute to 400 mL with reagent grade water, mix well and stopper.

Note: This solution tends to precipitate out Sn(OH)Cl with prolonged exposure to air. It should be prepared fresh daily, if possible. If this solution needs to be made up ahead of time, it should be stored in a container that can be closed against atmospheric gases. Precipitation of solid materials can often be controlled by adding a small amount of elemental tin to the bottom of the container.

e. 0.5 N Sulfuric Acid Solution:

Slowly add 14 mL of concentrated sulfuric acid to 900 mL of water, mix and dilute to 1000 mL with water in a 1 L volumetric flask.

D. STANDARD(S)

Note: Equivalent standards / solutions may be substituted. Purity and counterions are to be taken into account when calculating standard concentrations. In-house prepared standards shall be assigned an expiration date that is no later than the stability stated in the method. The maximum length of time that an in-house prepared standard shall be used is 1 year unless the laboratory has produced extension data.

1. Standard Information

Primary Mercury Standard, Catalog Number MSHG-10PPM, Inorganic Ventures, 300 Technology Drive, Christiansburg, VA 24073. Alternative concentrations and manufacturers are permissible with proper documentation.

2. Preparation of Standard Solution(s)

Stock Standard/ Fortification Standard (1.00 µg/mL):

Pipet 5.00 \pm 0.01 mL of the 10 μ g/mL primary standard into a 50 mL volumetric flask, add 5 mL concentrated HNO3, and bring to volume with reagent grade water.

The stock standard expires one year from the date of production when it's been stored refrigerated at 2 - 8 °C.

3. Preparation of Calibration Curve

Prepare Calibration Solutions by pipetting 0, 150, 300 and 600 µL of the Fortification Standard into four separate 300 mL BOD bottles. These four solutions are equivalent to

CLG-MERC1.02		Page 5 of 10
Title: Determination of Mercury by Atomic Absorption Spectroscopy		
Revision: 02	Replaces: CLG-MERC1.01	Effective: 04/13/2018

0, 0.5, 1.0, and 2.0 ppm, respectively. Continue with F.2.b.

E. SAMPLE PREPARATION

Process tissue until homogeneous. All samples are stored refrigerated or frozen until analyzed.

F. ANALYTICAL PROCEDURE

- 1. Preparation of Controls and Samples
 - a. Tissue Blank Weigh 0.30 ± 0.10 g of homogenized, known blank tissue into a 300 mL BOD bottle and stopper until use.
 - b. Recovery Sample Weigh 0.30 ± 0.10 g of homogenized sample into a 300 mL BOD bottle. Fortify the sample with 0.30 µg of Hg in solution (equivalent to 1.0 ppm). If using the 1.00 µg/mL Hg Fortification Standard, spike with 300 µL.
 - c. Internal Check Sample Weigh 0.30 ± 0.10 g of homogenized sample into a 300 mL BOD bottle. Fortify the sample with 0.00 μ g of Hg or any concentration between 0.15 0.60 μ g (0.5 2.0 ppm) of Hg in solution.
 - d. Reagent blank

2. Extraction Procedure

- a. Weigh 0.30 ± 0.10 g of homogenized sample into a 300 mL BOD bottle and stopper until use.
- b. To the BOD bottles, add 4 mL of conc. H₂SO₄ and 1 mL of conc. HNO₃. Mix the contents thoroughly.
- c. Place the BOD bottles in a water bath set at 80 ± 5 °C for 30 mins. (Until samples completely dissolve.)
- d. Remove the BOD bottles from the hot water bath and allow the contents to cool to room temperature. This process may be speeded by the use of a cold water bath.
- e. Note: This next step adds solutions that are mostly water to the very acidic solutions contained in the BOD bottles. Caution should be exercised. Cautiously and slowly add 5 mL of 5% potassium permanganate solution to the BOD bottles, stopper and swirl to mix. Further add an additional 10 mL of 5% potassium permanganate followed by 8 mL of 5% potassium persulfate to the BOD bottles. Stopper and swirl to mix.
- f. Place the BOD bottles in a water bath set at 30 ± 5 °C for 90 mins.
- g. Remove the BOD bottles from the water bath and cool to room temperature, and add 50 mL of water to each BOD bottle. Swirl to mix the contents thoroughly.

CLG-MERC1.02		Page 6 of 10
Title: Determination of Mercury by Atomic Absorption Spectroscopy		
Revision: 02	Replaces: CLG-MERC1.01	Effective: 04/13/2018

Stopping point: The contents of the BOD bottles are quite stable at this point and may be stored at room temperature for up to a week.

h. Swirl to mix the contents thoroughly and pipet 10 mL of the contents from each BOD bottle into separate, clean, 15 mL polypropylene centrifuge tubes.

Note: Care should be exercised to avoid transferring any bottom sediment or floating fatty material that may exist in the BOD bottles.

i. Add 750 μL of 12% hydroxylamine solution to each 15 mL centrifuge tube and mix the contents thoroughly.

Note: Any existing solution color should disappear. If solution color does not disappear, add 25 μ L aliquots of 12% hydroxylamine solution until solution is colorless.

j. The 15 mL centrifuge tubes are transferred to the FIMS autosampler. A predetermined amount of solution is removed by the instrument and reduced with 10% stannous chloride solution. Any resulting elemental mercury is swept by carrier gas into the FIMS instrument for measurement and quantification.

3. Instrumental Settings

Note: The instrument parameters may be optimized to ensure system suitability. Set up the AAS according to the manufacturer's instructions.

a. Operating parameters for Perkin-Elmer FIMS-400.

Lamp: Hg

Wavelength: 253.7 nm

b. Pump Operating parameters for FIMS-400.

		Pump I	Pump 2		
Step #	Time (s)	(rpm)	(rpm)	<u>Valve</u>	Read (s)
Prefill	15	100	120	Fill	
1	10	100	120	Fill	
2	15	0	120	Iniect	25

Individual settings may be adjusted to obtain best results on any given day.

Note: It is also permissible to use an AA instrument that generates mercury hydride instead of elemental mercury generated in this example. Follow manufacturer's instructions when setting up such a system.

4. Injection sequence /Sample Set

CLG-MERC1.02		Page 7 of 10
Title: Determination of Mercury I	ру	
Revision: 02	Replaces: CLG-MERC1.01	Effective: 04/13/2018

Each sample set must contain one QA sample/20 samples:

- a. Calibration Standard curve at 0.00, 0.15, 0.30 and 0.60 µg of Hg, (equivalent to 0, 0.5, 1.0, and 2.0 ppm in tissue).
- b. Reagent Blank.
- c. Tissue Blank.
- d. Recovery.
- e. Internal check (if needed).
- f. Samples.
- g. Reinjection of standard/recovery for system suitability.

G. CALCULATIONS / IDENTIFICATION

- 1. The instrument controlling software is capable of performing all of the calculations needed for this analysis.
- 2. Quantitation may be performed by following the steps outlined below. Either peak height or peak area may be used for calculations.
- 3. Construct a linear regression line for the calibration solutions. The µg of Hg known to be in the solution should be plotted against the instrument response for each calibration solution.

The equation is y = mx + b

Where:

 $x = \mu g$ of Hg in the original calibration solution.

y = Instrument response.

m = calculated slope of the regression line.

b = calculated y intercept of the regression line.

4. Calculate the percent recovery for any recovery (or internal check) samples according to the following formula...

$$\% \, Recovery = \left[\left\{ \left[\frac{\left(Resp_{Rec} - b \right)}{m} \middle/ Wt_{Rec} \right] - \left[\frac{\left(Resp_{Mtrx\,Blk} - b \right)}{m} \middle/ Wt_{Mtrx\,Blk} \right] \right\} \middle/ (\mu g/g) \text{Fortified Hg} \right] * 100\%$$

Resp_{Rec} = Instrument response for a recovery (or internal check) sample.

CLG-MERC1.02		Page 8 of 10
Title: Determination of Mercury by Atomic Absorption Spectroscopy		
Revision: 02	Replaces: CLG-MERC1.01	Effective: 04/13/2018

 $Resp_{Mtrx Blk}$ = Instrument response for the matrix blank sample.

Wt_{Rec} = Original weight of recovery sample in grams.

Wt_{Blk} = Original weight of blank tissue in grams.

 $(\mu g/g)_{\text{Fortified Hg}} = \text{Original fortified level of Hg in a recovery (or internal check)}$ sample assuming the original weight of the sample was 0.20 g.

5. Samples that have extracted solutions with total mercury concentrations in excess of 2.00 ppm of Hg in solution should be re-run with calibration standards that bracket the sample concentration. Calibration Solutions with levels of Hg as high as 5.00 ppm in solution are permissible without loss of linearity in the calibration curve. Should a sample have a level of Hg above 5.00 ppm in solution, dilution of the final sample extract is also a permissible means of keeping the final sample concentration within the scale of the calibration standards.

H. SAFETY INFORMATION AND PRECAUTIONS

- 1. Required Protective Equipment Safety glasses, appropriate gloves, lab coat.
- 2. Hazards

Procedure Step	Hazard	Recommended Safe Procedures
Hydroxylamine Hydrochloride	Corrosive. Will cause burns to all body tissue. May be fatal if swallowed or inhaled. Possible skin sensitizer.	Isolate from sources of ignition and oxidizing materials
Hydroxylamine Sulfate	Corrosive. Causes burns. Harmful if swallowed. Dangerous for the environment. Avoid breathing in dust. Avoid contact with eyes, skin and clothing.	Prepare solutions in a fume hood.
Mercury Standard, 10 ppm in 10% HCI	Corrosive. Causes burns. Harmful if swallowed. Vapors may irritate to eyes, nose, throat and lungs. Avoid contact with eyes, skin and clothing.	Prepare solutions in a fume hood.
Nitric Acid, Sulfuric Acid	Will cause severe burns to all body tissue. May be fatal if swallowed or inhaled.	Prepare solutions in a fume hood. Store out of direct sunlight. Regulate contact with

CLG-MERC1.02		Page 9 of 10
Title: Determination of Mercury by Atomic Absorption Spectrosco		ру
Revision: 02	Replaces: CLG-MERC1.01	Effective: 04/13/2018

heat, water, and incompatible materials.

Potassium Oxidizer, contact with reducing Persulfate

agents or combustibles may cause ignition. Irritant to eyes, respiratory system and skin. Avoid breathing in dust. Avoid contact with eyes, skin and

Prepare solutions in a fume hood. Avoid contact with combustible materials.

Prepare solutions in a fume

hood. Avoid contact with

combustible materials.

clothing.

Potassium Permanganate Oxidizer, contact with reducing agents or combustibles may cause ignition or extremely violent combustion. Causes burns to all

tissue. Toxic metal fumes may form when heated to

decomposition.

Stannous Chloride

Corrosive. Causes burns. Harmful if ingested. Avoid breathing in dust. Avoid contact with eyes, skin and clothing.

Prepare solutions in a fume

hood.

Stannous Sulfate

Irritant to eyes, respiratory system and skin. Avoid breathing in dust. Avoid contact with eyes, skin and clothing.

Prepare solutions in a fume

hood.

3. **Disposal Procedures**

Follow local, state and federal guidelines for disposal.

I. **QUALITY ASSURANCE PLAN**

Performance Standard 1.

	Analytical Range	Acceptable	Acceptable Repeatability
Analyte	(ppm Hg)	Recovery (%)	(% CV)
Mercury	0.20 - 5.00	85 - 115	≤ 10

Acceptability criteria: a.

- i. Correlation coefficient \geq 0.995.
- ii. No false positive or false negative results.

CLG-MERC1.02	Page 10 of 10			
Title: Determination of Mercury by Atomic Absorption Spectroscopy				
Revision: 02	Replaces: CLG-MERC1.01	Effective: 04/13/2018		

2. Critical Control Points and Specifications

Record Acceptable Control

a. Reagent Blank Absorbance should produce a response ≤ 0.1

ppm, (equivalent concentration in tissue). If

greater, check for cleanliness and

contamination of glassware and reagents.

b. Tissue dissolution (F.1.c) The tissue must be observed to completely

dissolve during the digestion phase of this

method.

- 3. Intralaboratory Check Samples
 - a. System, minimum contents.
 - i. Frequency: One per week per analyst when samples analyzed.
 - ii. Records are to be maintained.
 - b. Acceptability criteria.

Refer to I. 1.

If unacceptable values are obtained, then:

- i. Investigate following established procedures.
- ii. Take corrective action as warranted.
- 4. Sample Condition upon Receipt Cold

J. APPENDIX

- 1. References
 - a. EPA Method 245.6, "Determination of Mercury in Tissues by Cold Vapor Atomic Absorption Spectrometry", Revision 2.3, April 1991.

Note: Matrices successfully verified using this method include fish of the order Siluriformes (catfish), bovine, swine, and chicken muscle; bovine, swine, and chicken liver; and processed products.

K. APPROVALS AND AUTHORITIES

- 1. Approvals on file.
- 2. Issuing Authority: Director, Laboratory Quality Assurance Staff